



泰安市远洋泵业有限公司

Tai'an Ocean Pump Co., Limited

Pump Model	Flow		Head	Rotation Speed	Power (kw)		Efficiency	Max. Allowed vacuum height	Impeller Dia.	Weight
	(m³/h)	(l/s)	(m)	(r/min)	Shaft	Electric Motor	(%)	(m)	(mm)	(kg)
6Sh-6 (150S78)	126	35	84	2900	40	55	72	5	248	150
	162	45	78		46.5		74			
	198	55	70		52.4		72			
6Sh-6A (150S78A)	112	31	67	2900	30	45	68	5	220	150
	144	40	62		33.8		72			
	180	50	55		38.5		70			
6Sh-9 (150S50)	130	36.2	52	2900	25.3	37	73.9	5	200	145
	170	47.2	47.6		27.6		79.8			
	220	61.2	35		31.3		67			
6Sh-9A (150S50A)	120	31	43.8	2900	18.5	30	72	5	186	145
	144	40	40		20.9		75			
	180	50	35		24.5		70			
8Sh-6 (200S95)	180	50	100	2900	81.8	110	60	4.5	284	245
	234	65	93.5		86.3		69			
	288	80	82.5		91.1		71			
8Sh-6A	160	44.5	85.1	2900	60.8	90	61	5.5	262	245
8Sh-9 (200S63)	213	60	69	2900	55	75	74	5.3	236	265
	288	80	62.5		61.3		79.5	4.5		
	351	97.5	50		67.8		70.5	3		
8Sh-9A (200S63A)	180	50	54.5	2900	41	55	65	5.5	220	265
	270	70	46		48.3		70	5		
	324	90	37.5		51		65	3.8		
8Sh-13 (200S42)	216	60	48	2900	34.9	45	81	5	204	219
	288	80	41.3		38.1		85	3.6		
	342	95	35		40.2		81	1.8		
8Sh-13A (200S42A)	198	55	43	2900	30.5	37	76	5.2	193	219
	270	75	36		33.1		80	4.2		
	310	86	31		34.4		76	3		
10Sh-6 (250S65)	360	100	71	1450	88.1	132	79	6	460	565
	486	135	65.1		112		77			
	612	170	56		129.6		72			
10Sh-6A (250S65A)	342	95	61	1450	72	110	79	6	430	565
	468	130	54		86		80			
	540	150	50		98		75			
10Sh-9 (250S39)	360	100	42.5	1450	55.5	75	75	6	367	428
	486	135	38.5		61.5		83			
	612	170	32.5		67.7		80			
10Sh-9A (250S39A)	324	90	35.5	1450	40.2	55	78	6	338	428
	468	130	30.5		45.7		85			
	576	160	25		47.8		82			
10Sh-13 (250S24)	360	100	27	1450	33.1	45	80	6	296	420
	486	135	23.5		36.2		86			
	576	160	19		36.4		82			

ADD: Mingtang Road, Tai'an city, Shandong province, China

Email: info@sandpumpmachine.com

Website: www.sandpumpmachine.com



泰安市远洋泵业有限公司

TAI'AN OCEAN PUMP CO., LIMITED

Pump Model	Flow		Head (m)	Rotation Speed (r/min)	Power (kw)		Efficiency (%)	Max. Allowed vacuum height (m)	Impeller Dia. (mm)	Weight (kg)
	(m³/h)	(l/s)			Shaft	Electric Motor				
10Sh-13A (250S24A)	342	95	22.2	1450	25.8	37	80	6	270	420
	414	115	20.3		27.6		83			
	482	134	17.4		28.6		80			
10Sh-19 (250S14)	360	100	17.5	1450	21.4	30	80	6	240	405
	486	135	14		21.8		85			
	576	160	11		22.1		78			
10Sh-19A (250S14A)	320	80	13.3	1450	15.4	22	78	6	224	405
	432	120	11		15.8		82			
	504	140	8.6		15.8		75			
12Sh-6 (300S90)	590	164	98	1450	213	300	74	5.4	540	847
	792	220	90		250		77.5	4.5		
	936	260	82		279		75	3.5		
12Sh-6A (300S90A)	576	160	86	1450	190	260	71	5.5	510	845
	755	210	78		217		74	4.7		
	918	255	70		246		71	3.6		
12Sh-6B (300S90B)	540	150	72	1450	151	260	70	5.6	475	845
	720	200	67		180		73	4.9		
	900	250	57		200		70	3.8		
12Sh-9 (300S58)	576	160	65	1450	127.5	180	80	4.5	435	572
	792	220	58		150		83.5	4.5		
	972	270	50		167.5		79	4.5		
12Sh-9A (300S58A)	530	147	55	1450	99.2	155	80	4.5	402	572
	720	200	49		116		83			
	893	248	42		131		78			
12Sh-9B (300S58B)	504	140	47.2	1450	82.5	135	79	4.5	378	572
	684	190	43		97.7		82			
	835	232	37		108		78			
12Sh-13 (300S32)	612	170	38	1450	76.2	90	83	4.5	352	809
	792	220	32.2		80.3		86.5			
	900	250	25.5		78.1		80.1			
12Sh-13A (300S32A)	550	153	31	1450	58.1	75	80	4.5	322	809
	720	200	26		60.7		84			
	810	225	20.5		58		78			
12Sh-19 (300S19)	612	170	23	1450	47.9	55	80	4.5	290	660
	792	220	19.4		51		82			
	935	260	14		47.6		75			
12Sh-19A (300S19A)	504	140	20	1450	34.8	45	79	4.5	262	660
	792	220	16		38.3		82			
	900	250	11.5		37.6		75			
12Sh-28 (300S12)	611	170	14.5	1450	30.3	37	80	4.5	248	660
	792	220	12		32		81			
	900	250	10		33.1		74			

ADD: Mingtang Road, Tai'an city, Shandong province, China

Email: info@sandpumpmachine.com

Website: www.sandpumpmachine.com



泰安市远洋泵业有限公司

TAI'AN OCEAN PUMP CO., LIMITED

Pump Model	Flow		Head (m)	Rotation Speed (r/min)	Power (kw)		Efficiency (%)	Max. Allowed vacuum height (m)	Impeller Dia. (mm)	Weight (kg)
	(m³/h)	(l/s)			Shaft	Electric Motor				
12Sh-28A (300S12A)	522	145	11.8	1450	22.4	30	75	4.5	225	660
	685	190	10		23.3		80			
	792	220	8.7		24.4		77			
14Sh-6 (350S125)	850	236	140	1470	462	680	70	3.5	655	1580
	1250	347	125		545		78			
	1663	461	100		625		72.5			
14Sh-6A (350S125 A)	800	223	125	1470	391	630	70	3.5	620	1580
	1180	328	112		462		78			
	1570	436	90		550		70			
14Sh-6B (350S125 B)	745	207	108	1470	313	500	70	3.5	575	1580
	1100	305	96		373		77			
	1460	405	77		422		72.5			
14Sh-9 (350S75)	972	270	80	1450	271	400	78	3.5	500	1200
	1260	350	75		314		82			
	1440	400	65		319		80			
14Sh-9A (350S75A)	900	250	70	1450	220	300	78	3.5	465	1200
	1170	325	65		247		84			
	1330	370	56		257		79			
14Sh-9B (350S75B)	826	230	59	1450	178	260	75	3.5	428	1200
	1080	300	55		198		82			
	1225	340	47.5		206		77			
14Sh-13 (350S44)	972	270	50	1470	164	220	81	3.5	410	1105
	1260	350	43.8		178		84			
	1480	410	37		188		79			
14Sh-13A (350S44A)	864	240	41	1470	121	180	80	3.5	380	1105
	1120	310	36		130		84			
	1330	370	30		136		80			
14Sh-19 (350S26)	971	270	32	1450	99.7	132	85	3.5	350	880
	1260	350	26		102		88			
	1440	400	22		95.7		82			
14Sh-19A (350S26A)	864	240	26	1450	76.5	110	80	3.5	326	880
	1120	310	21.5		77		85			
	1296	360	16.5		80		73			
14Sh-28 (350S16)	971	270	20	1450	66.2	75	80	3.5	290	760
	1260	350	16.2		68.5		81			
	1440	400	13.4		71		74			



泰安市远洋泵业有限公司

Tai'an Ocean Pump Co., Limited

Pump Model	Flow		Head	Rotation Speed	Power (kw)		Efficiency	Max. Allowed vacuum height	Impeller Dia.	Weight
	(m³/h)	(l/s)	(m)	(r/min)	Shaft	Electric Motor	(%)	(m)	(mm)	(kg)
14Sh-28A (350S16A)	864	240	16	1450	51	55	74	3.5		760
	1044	290	13.4		48.8		78			
	1260	350	10		49		70			
20Sh-6 (500S98)	1450	403	108	970	585	800	72.5	4	860	4330
	2016	560	98.4		680		79.5			
	2300	640	89		735		76			
20Sh-6A (500S98A)	1349	375	93	970	490	630	70	3.6	800	4330
	1870	520	85		564		77			
	2140	595	77		607		74			
20Sh-9 (500S59)	1150	430	66	970	340	500	82	4	682	2750
	2016	560	59		390		83			
	2450	680	50		433		77			
20Sh-9A (500S59A)	1405	390	58	970	300	400	74	4	640	2750
	1910	530	50		347		75			
	2270	630	42		360		72			
20Sh-9B (500S59B)	1763	490	42	970	275	355	74	4	600	2750
20Sh-13 (500S35)	1550	430	40	970	206	280	82	4	550	2340
	2016	560	35.1		219		88			
	2410	670	30		247		80			
20Sh-13A (500S35A)	1870	520	31	970	186	240	85	4	510	2340
20Sh-19 (500S22)	1620	450	27	970	148	180	80	4	465	2010
	2016	560	22		117		82			
	2340	650	15		137		70			
20Sh-19A (500S22A)	1296	360	23	970	111	130	73	4	427	2010
	1870	520	17		108		80			
	2016	560	14		101		76			
20Sh-28 (500S13)	1620	450	15.2	970	78.9	110	85	4	390	2000
	2016	560	12.8		79		89			
	2325	646	10.6		78		86			
24Sh-9 (600S75)	3420	950	71	960	727	900	91	1.3	765	4300



泰安市远洋泵业有限公司

TAI'AN OCEAN PUMP CO., LIMITED

Pump Model	Flow		Head	Rotation Speed	Power (kw)		Efficiency	Max. Allowed vacuum height	Impeller Dia.	Weight
	(m³/h)	(l/s)	(m)	(r/min)	Shaft	Electric Motor	(%)	(m)	(mm)	(kg)
24Sh-9A (600S75A)	3168	880	61	960	585	710	90	2.5	710	4300
24Sh-9(J) (600S39)	2700	750	39	730	319	380	90	4.8	765	4300
24Sh-13 (600S47)	2502	695	56	970	460	550	83	2.5	630	3200
	3168	880	47.4		465		88			
	3499	972	38		426		80			
24Sh-19 (600S32)	2480	700	37	970	295	380	86	2.5	540	2550
	3170	880	32		310		69			
	3960	1100	22		279		85			
24Sh-19A (600S32A)	2304	640	31.5	970	235	280	84	2.5	500	2550
	2880	800	27		238		89			
	3600	1000	20		231		85			
24Sh-28 (600S22)	2340	650	23.5	970	187	250	80	2.5	450	2500
	2880	800	21		195		84.5			
	3420	950	18		207		81			
24Sh-28A (600S22A)	2340	650	17.5	970	145	185	77	2.5	415	2500
	2880	800	15.5		148		82			
	3420	950	13		154		78.5			
32Sh-19 (800S32)	4700	1305	35	730	575	630	78	3.5	740	5100
	5500	1530	32.5		580		84			
	6010	1670	28.9		567		83.5			
	6460	1795	25.4		567		80.4			
32Sh-19A (800S32A)	4550	1260	31	730	492	560	78	3.5	715	5100
	5310	1475	29		500		84			
	5800	1600	26.5		496		83.5			
	6250	1735	23		487		80.4			